



Max. Advance:

- 0 -> 14,0°
- 1 -> 16,0°
- 2 -> 18,0°
- 3 -> 20,0°
- 4 -> 22,0°
- 5 -> 24,0°
- 6 -> 26,0°
- 7 -> 28,0°
- 8 -> 30,0°
- 9 -> 32,0°
- A -> 34,0°
- B -> 36,0°
- C -> 38,0°
- D -> 40,0°
- E -> 42,0°
- F -> 44,0°

@ RPM

- 0 -> 4800
- 1 -> 4600
- 2 -> 4400
- 3 -> 4200
- 4 -> 4000
- 5 -> 3800
- 6 -> 3600
- 7 -> 3400
- 8 -> 3200
- 9 -> 3000
- A -> 2800
- B -> 2600
- C -> 2400
- D -> 2200
- E -> 2000
- F -> 1800

Engine Mode:

- 0 -> V2-engine dual-fire or single-fire (2 Sensors), HD legacy mode
- 1 -> 1-cylinder & 2-cylinder distributorless engines (2 Sensors)
- 2 -> 2-cylinder & 4-cylinder distributorless engines (2 Sensors)
- 3 -> 3-cyl. engines with distributor
- 4 -> 4-cyl. engines with distributor
- 5 -> 5 cyl. engines with distributor
- 6 -> 6 cyl. engines with distributor
- 7 -> 7 cyl. engines with distributor
- 8 -> 8 cyl. engines with distributor
- 9 -> 9 cyl. engines with distributor
- A -> 10 cyl. engines with distributor
- B -> 11 cyl. engines with distributor
- C -> 12 cyl. engines with distributor
- D -> reserved setting
- E -> reserved setting
- F -> reserved setting

